Code No. LIT-1927025
Issued April 2018

A19 Series Special Purpose Thermostat (Rubber-Coated Bulb and Capillary) Catalog Page

Description

This thermostat's rubber-coated bulb is designed for direct immersion.

Features

The rubber-coated bulb and capillary provide corrosion resistance.

Applications

This control is designed for use in cooling towers.

Technical Specifications

Maximum bulb temperature is 140°F (60°C).

Electrical Ratings

Motor Ratings VAC	120	208	240
AC Full Load A	6.0	3.4	3.0
AC Locked Rotor A	36.0	20.4	18.0
Non-Inductive or Resistance Load A (not lamp loads)	10 A, 120 to 277 VAC		
Pilot Duty	125 VA, 24 to 277 VAC		



A19AAF-4 Thermostat

Selection Charts

A19 Series Special Purpose Thermostat (Rubber-Coated Bulb and Capillary)

Product Code Number	Switch Action	Range °F (°C)	Differential F° (C°)	Bulb and Capillary	Range Adjuster	Maximum Bulb Temp. °F (°C)
A19AAF-4C	Single-Pole, Double Throw (SPDT)	40 to 90 (4 to 32)	1-1/2 (0.8)	3/8 in. x 5-3/4 in. rubber-coated 6 ft. capillary	Screwdriver slot	140 (60)

Replacement Parts

Product Code Number	Description
CVR28A-617R	Concealed adjustment cover
CVR28A-618R	Visible scale cover
KNB20A-602R	Knob Kit

The performance specifications are nominal and conform to acceptable industry standards. For applications at conditions beyond these specifications, consult the local Johnson Controls office. Johnson Controls shall not be liable for damages resulting from misapplication or misuse of its products. © 2018 Johnson Controls.