FFAL-A17Z-CFV-072

HFC, R-404A, 60Hz, 1- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	19.1
Unit Length (in):	24.9
Unit Width (in):	20.4
Ship Weight (lbs):	117.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	18.7
Compressor:	ZF07KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	75.0
Compressor LRA - Half winding:	
Compressor RLA:	13.9
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	21-Oct-2020			Return Gas Temp. (°F):	40
Compressor:	ZF07KAE-PFV-118	x	1	Subcooling (°F):	5
Performance No:	19423			Air Flow Rate (CFM)	1216

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-40	4,810	98.0	8.0	2.9
-35	5,620	99.1	9.1	3.2
-30	6,440	100.1	10.1	3.5
-25	7,290	101.2	11.2	3.8
-20	8,180	102.3	12.3	4.1
-15	9,130	103.6	13.6	4.4
-10	10,100	105.0	15.0	4.7
-5	11,200	106.4	16.4	5.0
0	12,400	108.1	18.1	5.3
5	13,700	109.9	19.9	5.6
10	15,100	111.8	21.8	6.0

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.