FFAL-A20Z-CFV-072

HFC, R-404A, 60Hz, 1- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	19.3
Unit Length (in):	34.0
Unit Width (in):	25.1
Ship Weight (lbs):	219.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	46.00

Electrical

Max Fuse Size:	35
Min Circuit Ampacity:	22.6
Compressor:	ZF08K4E-PFV-231
Compressor LRA - Low:	
Compressor LRA - High:	73.0
Compressor LRA - Half winding:	
Compressor RLA:	16.4
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	21-Oct-2020			Return Gas Temp. (°F):	40
Compressor:	ZF08K4E-PFV-231	x	1	Subcooling (°F):	5
Performance No:	19627			Air Flow Rate (CFM)	1490

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-40	5,990	99.7	9.7	2.8
-35	6,810	100.3	10.3	3.2
-30	7,690	100.9	10.9	3.5
-25	8,640	101.6	11.6	3.9
-20	9,670	102.4	12.4	4.2
-15	10,800	103.2	13.2	4.6
-10	11,900	104.1	14.1	4.9
-5	13,200	105.2	15.2	5.2
0	14,600	106.2	16.2	5.6

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.