FFAL-A26Z-TFC-072

HFC, R-404A, 60Hz, 3- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	19.3
Unit Length (in):	34.0
Unit Width (in):	25.1
Ship Weight (lbs):	175.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	45.00

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	19.8
Compressor:	ZF11K4E-TF5-231
Compressor LRA - Low:	
Compressor LRA - High:	88.0
Compressor LRA - Half winding:	
Compressor RLA:	14.2
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	21-Oct-2020			Return Gas Temp. (°F):	40
Compressor:	ZF11K4E-TF5-231	x	1	Subcooling (°F):	5
Performance No:	19667			Air Flow Rate (CFM)	1490

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-40	8,040	101.2	11.2	3.4
-35	9,130	102.0	12.0	3.8
-30	10,300	102.8	12.8	4.1
-25	11,500	103.8	13.8	4.5
-20	12,900	104.8	14.8	4.9
-15	14,300	105.9	15.9	5.2
-10	15,800	107.1	17.1	5.6
-5	17,400	108.5	18.5	5.9
0	19,100	109.9	19.9	6.2

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.