FFAL-A26Z-TFC-072

HFC , R-407A, 60Hz, 3- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	19.3
Unit Length (in):	34.0
Unit Width (in):	25.1
Ship Weight (lbs):	175.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	45.00

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	19.8
Compressor:	ZF11K4E-TF5-231
Compressor LRA - Low:	
Compressor LRA - High:	88.0
Compressor LRA - Half winding:	
Compressor RLA:	14.2
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	21-Oct-2020			Return Gas Temp. (°F):	40
Compressor:	ZF11K4E-TF5-231	x	1	Subcooling (°F):	5
Performance No:	19668			Air Flow Rate (CFM)	1490

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-40	6,640	103.4	13.4	2.8
-35	7,400	104.1	14.1	3.0
-30	8,430	105.0	15.0	3.4
-25	9,670	106.1	16.1	3.8
-20	11,100	107.3	17.3	4.2
-15	12,600	108.7	18.7	4.6
-10	14,100	110.1	20.1	5.0
-5	15,600	111.5	21.5	5.3
0	17,100	112.9	22.9	5.7

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.