FFAL-A26Z-TFC-072

HFO, R-448A, 60Hz, 3- Phase, 208/230 V

COPELAND

Availability : Custom US OEM Or Wholesaler NOTE :APPLICATION APPROVAL REQUIRED

Mechanical

Unit Height (in):	19.3
Unit Length (in):	34.0
Unit Width (in):	25.1
Ship Weight (lbs):	175.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	45.00

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	19.8
Compressor:	ZF11K4E-TF5-231
Compressor LRA - Low:	
Compressor LRA - High:	88.0
Compressor LRA - Half winding:	
Compressor RLA:	14.2
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	21-Oct-2020			Return Gas Temp. (°F):	40
Compressor:	ZF11K4E-TF5-231	x	1	Subcooling (°F):	5
Performance No:	19669			Air Flow Rate (CFM)	1490

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-40	6,880	105.2	15.2	2.9
-35	7,870	106.1	16.1	3.3
-30	8,960	107.1	17.1	3.6
-25	10,100	108.2	18.2	4.0
-20	11,500	109.3	19.3	4.4
-15	12,900	110.6	20.6	4.8
-10	14,400	112.0	22.0	5.2
-5	16,000	113.6	23.6	5.6
0	17,800	115.2	25.2	6.0

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.