FFAM-A10Z-CFV-072

HFC, R-404A, 60Hz, 1- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	16.5
Unit Length (in):	24.1
Unit Width (in):	18.3
Ship Weight (lbs):	102.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	21.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	8.9
Compressor:	ZB07KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	48.0
Compressor LRA - Half winding:	
Compressor RLA:	6.3
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	12-Nov-2019			Return Gas Temp. (°F):	40
Compressor:	ZB07KAE-PFV-118	x	1	Subcooling (°F):	5
Performance No:	16950			Air Flow Rate (CFM)	696

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-5	4,590	101.3	11.3	4.6
0	5,200	102.3	12.3	5.1
5	5,840	103.4	13.4	5.6
10	6,520	104.6	14.6	6.2
15	7,250	105.9	15.9	6.7
20	8,020	107.3	17.3	7.3
25	8,840	108.8	18.8	7.9

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.