FFAM-A10Z-CFV-072

HFO, R-448A, 60Hz, 1- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	16.5
Unit Length (in):	24.1
Unit Width (in):	18.3
Ship Weight (lbs):	102.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	21.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	8.9
Compressor:	ZB07KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	48.0
Compressor LRA - Half winding:	
Compressor RLA:	6.3
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	12-Nov-2019			Return Gas Temp. (°F):	40
Compressor:	ZB07KAE-PFV-118	x	1	Subcooling (°F):	5
Performance No:	16956			Air Flow Rate (CFM)	696

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-5	4,240	106.9	16.9	4.4
0	4,780	107.8	17.8	4.8
5	5,370	108.8	18.8	5.2
10	6,010	109.9	19.9	5.7
15	6,710	111.0	21.0	6.3
20	7,460	112.3	22.3	6.8
25	8,250	113.6	23.6	7.4

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.