FFAM-A12Z-TFC-072

HFC, R-404A, 60Hz, 3- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	16.5
Unit Length (in):	24.1
Unit Width (in):	18.3
Ship Weight (lbs):	104.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	21.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	8.0
Compressor:	ZB08KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	37.8
Compressor LRA - Half winding:	
Compressor RLA:	5.3
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	12-Nov-2019	Return Gas Temp. (°F):	40
Compressor:	ZB08KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	17010	Air Flow Rate (CFM)	1070

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-5	5,560	99.9	9.9	4.8
0	6,240	100.8	10.8	5.2
5	6,950	101.7	11.7	5.7
10	7,700	102.7	12.7	6.3
15	8,500	103.8	13.8	6.8
20	9,370	104.9	14.9	7.5
25	10,300	106.2	16.2	8.1

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.