FFAM-A12Z-TFC-072

HFO, R-449A, 60Hz, 3- Phase, 208/230 V

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	16.5
Unit Length (in):	24.1
Unit Width (in):	18.3
Ship Weight (lbs):	104.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	21.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	8.0
Compressor:	ZB08KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	37.8
Compressor LRA - Half winding:	
Compressor RLA:	5.3
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	12-Nov-2019			Return Gas Temp. (°F):	40
Compressor:	ZB08KAE-TF5-118	x	1	Subcooling (°F):	5
Performance No:	17018			Air Flow Rate (CFM)	1070

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-5	5,110	104.8	14.8	4.5
0	5,730	105.7	15.7	4.9
5	6,420	106.6	16.6	5.4
10	7,190	107.6	17.6	5.9
15	8,030	108.7	18.7	6.4
20	8,930	109.9	19.9	7.0
25	9,890	111.2	21.2	7.6

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.