FFAP-A17Z-CFV-072

HFC, R-134a, 60Hz, 1- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	16.6
Unit Length (in):	24.1
Unit Width (in):	18.4
Ship Weight (lbs):	109.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

Electrical

Max Fuse Size:	25
Min Circuit Ampacity:	17.1
Compressor:	ZS11KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	55.0
Compressor LRA - Half winding:	
Compressor RLA:	12.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	30-Dec-2019			Return Gas Temp. (°F):	40
Compressor:	ZS11KAE-PFV-118	x	1	Subcooling (°F):	5
Performance No:	17920			Air Flow Rate (CFM)	1070

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-5	4,400	100.4	10.4	4.9
0	5,030	100.4	10.4	5.5
5	5,720	100.4	10.4	6.1
10	6,440	101.1	11.1	6.7
15	7,210	102.3	12.3	7.3
20	8,030	103.7	13.7	7.9
25	8,920	105.1	15.1	8.6

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.