FFAP-A17Z-CFV-072

HFC, R-407C, 60Hz, 1- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	16.6
Unit Length (in):	24.1
Unit Width (in):	18.4
Ship Weight (lbs):	109.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.87 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	19.00

Electrical

Max Fuse Size:	25
Min Circuit Ampacity:	17.1
Compressor:	ZS11KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	55.0
Compressor LRA - Half winding:	
Compressor RLA:	12.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	30-Dec-2019			Return Gas Temp. (°F):	40
Compressor:	ZS11KAE-PFV-118	x	1	Subcooling (°F):	5
Performance No:	17926			Air Flow Rate (CFM)	1070

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-5	5,800	106.0	16.0	4.1
0	6,820	107.3	17.3	4.8
5	7,860	108.7	18.7	5.4
10	8,940	110.1	20.1	6.0
15	10,000	111.6	21.6	6.5
20	11,200	113.2	23.2	7.1
25	12,400	114.8	24.8	7.7

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.