# FFAP-A32Z-CFV-072

HFC, R-134a, 60Hz, 1- Phase, 208/230 V

COPELAND

**Availability :** **Custom US OEM Or Wholesaler**

## Mechanical

| | |
|---|---|
| Unit Height (in): | 18.9 |
| Unit Length (in): | 34.1 |
| Unit Width (in): | 25.1 |
| Ship Weight (lbs): | 188.0 |
| Condensor Type: | Air |
| CopeVap Water Storage: | NA |
| Liquid Connection Size (in)/Type: | 0.37 SWEAT |
| Suction Connection Size (in)/Type: | 1.12 SWEAT |
| Discharge Line Size (in): | 0.5 |
| Water Inlet (in): | |
| Water Outlet (in): | |
| Oil Type: | POE |
| Oil Recharge Amount (oz): | 34.00 |

## Electrical

| | |
|---|---|
| Max Fuse Size: | 50 |
| Min Circuit Ampacity: | 31.8 |
| Compressor: | ZS21KAE-PFV-118 |
| Compressor LRA - Low: | |
| Compressor LRA - High: | 112.0 |
| Compressor LRA - Half winding: | |
| Compressor RLA: | 23.2 |
| UL: | Listed |
| UL File #: | SA633 |
| UL Guide Card: | LZFE |
| Amps Per Motor: | 1.1 |
| Fan Motor Quantity: | 2 |

## Air - Cooled Unit Performance

| | | | | | |
|---|---|---|---|---|---|
| Release Date: | 30-Dec-2019 | | | Return Gas Temp. (°F): | 40 |
| Compressor: | ZS21KAE-PFV-118 | x | 1 | Subcooling (°F): | 5 |
| Performance No: | 17776 | | | Air Flow Rate (CFM) | 2170 |

### 90°F Ambient Air Temperature

| Evap Temp (°F) | Unit Capacity (Btu/hr) | Cond. Temp. (°F) | Temp. Diff. (°F) | EER (Btu/Wh): |
|---|---|---|---|---|
| -5 | 9,190 | 100.4 | 10.4 | 5.2 |
| 0 | 10,500 | 100.4 | 10.4 | 5.9 |
| 5 | 11,900 | 100.4 | 10.4 | 6.5 |
| 10 | 13,400 | 101.5 | 11.5 | 7.1 |
| 15 | 15,000 | 102.7 | 12.7 | 7.8 |
| 20 | 16,700 | 104.0 | 14.0 | 8.4 |
| 25 | 18,600 | 105.4 | 15.4 | 9.1 |



Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.