FFAP-A32Z-TFC-072

HFC, R-134a, 60Hz, 3- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	18.9
Unit Length (in):	34.1
Unit Width (in):	25.1
Ship Weight (lbs):	188.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	1.12 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	34.00

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	21.8
Compressor:	ZS21KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	93.0
Compressor LRA - Half winding:	
Compressor RLA:	15.2
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	30-Dec-2019			Return Gas Temp. (°F):	40
Compressor:	ZS21KAE-TF5-118	x	1	Subcooling (°F):	5
Performance No:	17800			Air Flow Rate (CFM)	2170

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-5	9,190	100.4	10.4	5.2
0	10,500	100.4	10.4	5.9
5	11,900	100.4	10.4	6.5
10	13,400	101.5	11.5	7.1
15	15,000	102.7	12.7	7.8
20	16,700	104.0	14.0	8.4
25	18,600	105.4	15.4	9.1

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.