FFAP-A40Z-CFV-072

HFC, R-407C, 60Hz, 1- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	26.6
Unit Length (in):	44.1
Unit Width (in):	28.3
Ship Weight (lbs):	247.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.5 SWEAT
Suction Connection Size (in)/Type:	1.12 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	34.00

Electrical

Max Fuse Size:	50
Min Circuit Ampacity:	33.1
Compressor:	ZS26KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	104.0
Compressor LRA - Half winding:	
Compressor RLA:	23.6
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	30-Dec-2019			Return Gas Temp. (°F):	40
Compressor:	ZS26KAE-PFV-118	x	1	Subcooling (°F):	5
Performance No:	18071			Air Flow Rate (CFM)	4240

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-5	13,600	104.9	14.9	4.2
0	16,000	105.8	15.8	4.9
5	18,500	106.7	16.7	5.6
10	21,000	107.6	17.6	6.3
15	23,700	108.6	18.6	6.9
20	26,500	109.6	19.6	7.6
25	29,400	110.6	20.6	8.3

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.