FFAP-A42Z-CFV-072

HFC, R-407C, 60Hz, 1- Phase, 208/230 V

COPELAND

Availability : **Custom US OEM Or Wholesaler**

Mechanical

Unit Height (in):	26.6
Unit Length (in):	44.1
Unit Width (in):	28.3
Ship Weight (lbs):	255.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.5 SWEAT
Suction Connection Size (in)/Type:	1.12 SWEAT
Discharge Line Size (in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	34.00

Electrical

Max Fuse Size:	60
Min Circuit Ampacity:	38.8
Compressor:	ZS33KAE-PFV-118
Compressor LRA - Low:	
Compressor LRA - High:	146.0
Compressor LRA - Half winding:	
Compressor RLA:	28.2
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	30-Dec-2019			Return Gas Temp. (°F):	40
Compressor:	ZS33KAE-PFV-118	x	1	Subcooling (°F):	5
Performance No:	18143			Air Flow Rate (CFM)	4240

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-5	16,600	106.4	16.4	4.3
0	19,600	107.5	17.5	5.0
5	22,600	108.6	18.6	5.6
10	25,800	109.7	19.7	6.3
15	29,000	110.9	20.9	6.9
20	32,400	112.2	22.2	7.6
25	35,900	113.5	23.5	8.3

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.