TracPipe CounterStrike Flexible Gas Piping by OmegaFlex PS-II

Product

AutoSnap® Straight Fitting (Female-NPT) Assembly for TracPipe® and TracPipe® CounterSTrike®

Project Information

Job Name:		Date Submitted:	
Location:		Submitted By:	
Engineer:		Approved By:	
Contractor:		Manufacturer's Rep:	

Installation

Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

Application Information

Transition fitting between TracPipe or CounterStrike Tubing and NPT thread. Fitting thread is Female NPT. For use indoors, outdoors, and concealed location applications.



Technical Data

Materials

Nut, Adapter, Flange and Snap Ring	Yellow Brass

Pressure Ratings (used with tubing)

Specification Operating Pressure	25 PSIG
CSA International Evaluation Report - Max Operating Pressure	
3/8" through 1-1/4"	125 PSIG

Temperature Ratings (used with tubing)

Operating Temperature Range	-20 to 200 Deg F

Codes

ICC Codes (IFGC, IRC, IMC), NFPA 54 / ANSI Z223.1, UPC, CAN/CSA B149.1, NFPA 58, UPC

Standards

ANSI LC1 / CSA 6.26, ANSI Z223.1

Listings

CSA, ICC PMG 1046 / 1052, IAPMO (UPC) File No. 4665

Dimensional Information

✓	Size	P/N	Diameter across flats (Nom. in.)	Fitting length (Nom. in.)	TracPipe or CounterStrike Size	Weight (lbs/ft)
☐	3/8" x 1/2"	FGP-SFSTF-375	7/8"		3/8"	0.25
☐	1/2"	FGP-SFSTF-500	1"		1/2"	0.29
☐	3/4"	FGP-SFSTF-750	1-1/4"		3/4"	0.43
☐	1"	FGP-FSTF-1000	1-3/4"		1"	0.78

OmegaFlex, Inc. * 451 Creamery Way* Exton, PA 19341
Tel: 610-524-7272 * Toll Free: 800-671-8622 * Fax: 610-524-7282
www.omegaflex.com

TracPipe, Counterstrike, PS-II, AutoFlare, and AutoTrip are registered trademarks of OmegaFlex, Inc.