M6GL-H079-CFA-177

HFO, R-449A, 60Hz, 1- Phase, 115 V

COPELAND

Availability : **Standard US OEM**

Mechanical

Unit Height (in):	11.8
Unit Length (in):	18.9
Unit Width (in):	14.3
Ship Weight (lbs):	59.0
Condensor Type:	
CopeVap Water Storage:	
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.5 SWEAT
Discharge Line Size (in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	13.00

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	15.1
Compressor:	RFT26C1E-IFA-102
Compressor LRA - Low:	
Compressor LRA - High:	66.0
Compressor LRA - Half winding:	
Compressor RLA:	10.7
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	09-Jan-2020	Return Gas Temp. (°F):	40
Compressor:	RFT26C1E-IFA-102 x 1	Subcooling (°F):	5
Performance No:	18223	Air Flow Rate (CFM)	450

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-30	1,500	103.1	13.1	2.8
-25	1,740	104.0	14.0	3.0
-20	2,040	105.0	15.0	3.3
-15	2,380	106.2	16.2	3.6
-10	2,770	107.6	17.6	3.9
-5	3,210	109.1	19.1	4.2
0	3,680	110.8	20.8	4.6

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.