M6GP-H074-CFA-179

HFC, R-407C, 60Hz, 1- Phase, 115 V

COPELAND

Availability : **Standard US OEM**

Mechanical

Unit Height (in):	11.8
Unit Length (in):	18.1
Unit Width (in):	14.3
Ship Weight (lbs):	48.0
Condensor Type:	
CopeVap Water Storage:	
Liquid Connection Size (in)/Type:	0.25 SWEAT
Suction Connection Size (in)/Type:	0.5 SWEAT
Discharge Line Size (in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	13.00

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	20.5
Compressor:	RST55C1E-CFA-102
Compressor LRA - Low:	
Compressor LRA - High:	70.0
Compressor LRA - Half winding:	
Compressor RLA:	15.0
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	23-Feb-2018	Return Gas Temp. (°F):	40
Compressor:	RST55C1E-CFA-102 x 1	Subcooling (°F):	5
Performance No:	14627	Air Flow Rate (CFM)	450

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	3,200	108.7	18.7	4.3
5	3,680	110.4	20.4	4.7
10	4,190	112.1	22.1	5.1
15	4,730	114.0	24.0	5.4
20	5,310	115.9	25.9	5.8
25	5,920	118.0	28.0	6.1
30	6,560	120.2	30.2	6.5

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.