M6JM-H023-IAA-177

HFO, R-448A, 60Hz, 1- Phase, 115 V

COPELAND

Availability : **Standard US OEM**

Mechanical

Unit Height (in):	11.4
Unit Length (in):	14.1
Unit Width (in):	11.4
Ship Weight (lbs):	47.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.25 SWEAT
Suction Connection Size (in)/Type:	0.37 SWEAT
Discharge Line Size (in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	10.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	6.7
Compressor:	ASE14C4E-IAA-103
Compressor LRA - Low:	
Compressor LRA - High:	34.00
Compressor LRA - Half winding:	
Compressor RLA:	4.8
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	11-Jan-2017	Return Gas Temp. (°F):	40
Compressor:	ASE14C4E-IAA-103 x 1	Subcooling (°F):	5
Performance No:	10236	Air Flow Rate (CFM)	201

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-10	857	103.3	13.3	3.4
-5	1,010	104.5	14.5	3.7
0	1,160	105.7	15.7	4.0
5	1,320	107.0	17.0	4.3
10	1,490	108.4	18.4	4.6
15	1,670	109.7	19.7	4.9
20	1,870	111.2	21.2	5.2
25	2,070	112.7	22.7	5.5
30	2,300	114.3	24.3	5.9

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.