M6JM-H043-IAA-177

HFO, R-448A, 60Hz, 1- Phase, 115 V

COPELAND

Availability : Standard US OEM

NOTE :APPLICATION APPROVAL REQUIRED

Mechanical

Unit Height (in):	11.4
Unit Length (in):	14.4
Unit Width (in):	11.4
Ship Weight (lbs):	40.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.25 SWEAT
Suction Connection Size (in)/Type:	0.37 SWEAT
Discharge Line Size (in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	10.00

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	13.1
Compressor:	ASE39C5E-IAA-103
Compressor LRA - Low:	
Compressor LRA - High:	47.0
Compressor LRA - Half winding:	
Compressor RLA:	10.0
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	11-Jan-2017	Return Gas Temp. (°F):	40
Compressor:	ASE39C5E-IAA-103 x 1	Subcooling (°F):	5
Performance No:	10958	Air Flow Rate (CFM)	201

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-5	2,450	115.9	25.9	4.7
0	2,530	117.1	27.1	4.4
5	2,750	119.1	29.1	4.4
10	3,070	121.6	31.6	4.6
15	3,450	124.4	34.4	4.8
20	3,850	127.4	37.4	5.0
25	4,250	130.4	40.4	5.1
30	4,620	133.3	43.3	5.1

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.