M6KP-0127-CFV-072

HFO, R-448A, 60Hz, 1- Phase, 208/230 V

COPELAND

Availability : **Standard US OEM**

Mechanical

Unit Height (in):	16.2
Unit Length (in):	24.0
Unit Width (in):	18.3
Ship Weight (lbs):	94.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.62 SWEAT
Discharge Line Size (in):	0.37
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	20.00

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	13.0
Compressor:	RST80C1E-PFV-150
Compressor LRA - Low:	
Compressor LRA - High:	46.0
Compressor LRA - Half winding:	
Compressor RLA:	9.3
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	1.1
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	11-Jan-2017	Return Gas Temp. (°F):	40
Compressor:	RST80C1E-PFV-150 x 1	Subcooling (°F):	5
Performance No:	10324	Air Flow Rate (CFM)	1070

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-10	4,470	104.0	14.0	4.2
-5	5,180	105.0	15.0	4.6
0	5,940	106.0	16.0	5.1
5	6,760	107.1	17.1	5.6
10	7,620	108.3	18.3	6.0
15	8,540	109.5	19.5	6.5
20	9,490	110.8	20.8	7.0
25	10,500	112.2	22.2	7.4
30	11,500	113.7	23.7	7.8

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.