# M6QM-H049-IAA-272

HFO, R-448A, 60Hz, 1- Phase, 115 V

COPELAND

**Availability :** Standard US OEM

NOTE :APPLICATION APPROVAL REQUIRED

## Mechanical

| | |
|---|---|
| Unit Height (in): | 11.4 |
| Unit Length (in): | 15.7 |
| Unit Width (in): | 12.1 |
| Ship Weight (lbs): | 43.0 |
| Condensor Type: | Air |
| CopeVap Water Storage: | NA |
| Liquid Connection Size (in)/Type: | 0.25 SWEAT |
| Suction Connection Size (in)/Type: | 0.37 SWEAT |
| Discharge Line Size (in): | 0.25 |
| Water Inlet (in): | |
| Water Outlet (in): | |
| Oil Type: | POE |
| Oil Recharge Amount (oz): | 10.00 |

## Electrical

| | |
|---|---|
| Max Fuse Size: | 20 |
| Min Circuit Ampacity: | 13.4 |
| Compressor: | ASE39C5E-IAA-103 |
| Compressor LRA - Low: | |
| Compressor LRA - High: | 47.0 |
| Compressor LRA - Half winding: | |
| Compressor RLA: | 10.0 |
| UL: | Recognized |
| UL File #: | SA633 |
| UL Guide Card: | LZFE2 |
| Amps Per Motor: | 0.53 |
| Fan Motor Quantity: | 1 |

## Air - Cooled Unit Performance

| | | | |
|---|---|---|---|
| Release Date: | 11-Jan-2017 | Return Gas Temp. (°F): | 40 |
| Compressor: | ASE39C5E-IAA-103 x 1 | Subcooling (°F): | 5 |
| Performance No: | 11209 | Air Flow Rate (CFM) | 220 |

### 90°F Ambient Air Temperature

| Evap Temp (°F) | Unit Capacity (Btu/hr) | Cond. Temp. (°F) | Temp. Diff. (°F) | EER (Btu/Wh): |
|---|---|---|---|---|
| -5 | 2,470 | 114.7 | 24.7 | 4.5 |
| 0 | 2,560 | 115.9 | 25.9 | 4.3 |
| 5 | 2,790 | 117.8 | 27.8 | 4.4 |
| 10 | 3,110 | 120.3 | 30.3 | 4.6 |
| 15 | 3,500 | 123.1 | 33.1 | 4.8 |
| 20 | 3,900 | 126.1 | 36.1 | 4.9 |
| 25 | 4,310 | 129.2 | 39.2 | 5.1 |
| 30 | 4,670 | 132.3 | 42.3 | 5.1 |



Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.