# M6ZP-0053-IAA-177

HFO, R-448A, 60Hz, 1- Phase, 115 V

COPELAND

**Availability :** Standard US OEM

NOTE :APPLICATION APPROVAL REQUIRED

## Mechanical

| | |
|---|---|
| Unit Height (in): | 11.8 |
| Unit Length (in): | 17.4 |
| Unit Width (in): | 13.5 |
| Ship Weight (lbs): | 57.0 |
| Condensor Type: | Air |
| CopeVap Water Storage: | NA |
| Liquid Connection Size (in)/Type: | 0.37 SWEAT |
| Suction Connection Size (in)/Type: | 0.5 SWEAT |
| Discharge Line Size (in): | 0.25 |
| Water Inlet (in): | |
| Water Outlet (in): | |
| Oil Type: | POE |
| Oil Recharge Amount (oz): | 13.00 |

## Electrical

| | |
|---|---|
| Max Fuse Size: | 20 |
| Min Circuit Ampacity: | 14.0 |
| Compressor: | RST45C1E-IAA-102 |
| Compressor LRA - Low: | |
| Compressor LRA - High: | 54.5 |
| Compressor LRA - Half winding: | |
| Compressor RLA: | 10.5 |
| UL: | Recognized |
| UL File #: | SA633 |
| UL Guide Card: | LZFE2 |
| Amps Per Motor: | 0.53 |
| Fan Motor Quantity: | 1 |

## Air - Cooled Unit Performance

| | | | |
|---|---|---|---|
| Release Date: | 03-May-2017 | Return Gas Temp. (°F): | 40 |
| Compressor: | RST45C1E-IAA-102 x 1 | Subcooling (°F): | 5 |
| Performance No: | 11336 | Air Flow Rate (CFM) | 330 |

### 90°F Ambient Air Temperature

| Evap Temp (°F) | Unit Capacity (Btu/hr) | Cond. Temp. (°F) | Temp. Diff. (°F) | EER (Btu/Wh): |
|---|---|---|---|---|
| -10 | 1,970 | 109.7 | 19.7 | 3.5 |
| -5 | 2,280 | 111.4 | 21.4 | 3.8 |
| 0 | 2,610 | 113.3 | 23.3 | 4.0 |
| 5 | 2,960 | 115.2 | 25.2 | 4.3 |
| 10 | 3,320 | 117.2 | 27.2 | 4.5 |
| 15 | 3,720 | 119.4 | 29.4 | 4.7 |
| 20 | 4,140 | 121.7 | 31.7 | 4.9 |
| 25 | 4,590 | 124.2 | 34.2 | 5.1 |
| 30 | 5,070 | 126.9 | 36.9 | 5.3 |



Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.