M6ZP-0053-IAV-177

HFC, R-407C, 60Hz, 1- Phase, 208/230 V

COPELAND

Availability : Standard US OEM

NOTE :APPLICATION APPROVAL REQUIRED

Mechanical

Unit Height (in):	11.8
Unit Length (in):	17.4
Unit Width (in):	13.6
Ship Weight (lbs):	57.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.37 SWEAT
Suction Connection Size (in)/Type:	0.5 SWEAT
Discharge Line Size (in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	13.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	7.2
Compressor:	RST45C1E-IAV-104
Compressor LRA - Low:	
Compressor LRA - High:	26.5
Compressor LRA - Half winding:	
Compressor RLA:	5.3
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	23-Feb-2018	Return Gas Temp. (°F):	40
Compressor:	RST45C1E-IAV-104 x 1	Subcooling (°F):	5
Performance No:	14756	Air Flow Rate (CFM)	330

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
5	2,700	113.7	23.7	4.1
10	3,070	115.8	25.8	4.4
15	3,470	118.0	28.0	4.6
20	3,910	120.4	30.4	4.9
25	4,360	122.9	32.9	5.2
30	4,840	125.6	35.6	5.4

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.