M7JH-H038-IAA-177

HFO, R-450A, 60Hz, 1- Phase, 115 V

COPELAND

Availability : **Standard US OEM**

Mechanical

Unit Height (in):	11.4
Unit Length (in):	14.4
Unit Width (in):	11.4
Ship Weight (lbs):	39.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.25 SWEAT
Suction Connection Size (in)/Type:	0.37 SWEAT
Discharge Line Size (in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	10.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	10.7
Compressor:	ARE48C5E-IAA-103
Compressor LRA - Low:	
Compressor LRA - High:	43
Compressor LRA - Half winding:	
Compressor RLA:	8.0
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	05-Jan-2017	Return Gas Temp. (°F):	65
Compressor:	ARE48C5E-IAA-103 x 1	Subcooling (°F):	5
Performance No:	12446	Air Flow Rate (CFM)	201

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
0	1,690	105.9	15.9	4.7
5	1,940	107.9	17.9	5.1
10	2,190	109.9	19.9	5.3
15	2,470	112.1	22.1	5.6
20	2,750	114.5	24.5	5.8
25	3,060	116.9	26.9	6.0
30	3,370	119.5	29.5	6.1
35	3,710	122.3	32.3	6.3
40	4,050	125.1	35.1	6.4
45	4,410	128.1	38.1	6.5

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.