M7KH-0060-CAV-177

HFC, R-134a, 60Hz, 1- Phase, 208/230 V

COPELAND

Availability : **Standard US OEM**

Mechanical

Unit Height (in):	13.1
Unit Length (in):	24.0
Unit Width (in):	16.4
Ship Weight (lbs):	73.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.25 SWEAT
Suction Connection Size (in)/Type:	0.5 SWEAT
Discharge Line Size (in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	13.00

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	9.2
Compressor:	RRT64C1E-IAV-104
Compressor LRA - Low:	
Compressor LRA - High:	31.0
Compressor LRA - Half winding:	
Compressor RLA:	6.4
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	11-May-2017	Return Gas Temp. (°F):	65
Compressor:	RRT64C1E-IAV-104 x 1	Subcooling (°F):	5
Performance No:	11581	Air Flow Rate (CFM)	695

90°F Ambient Air Temperature

Evap Temp (°F)	Unit Capacity (Btu/hr)	Cond. Temp. (°F)	Temp. Diff. (°F)	EER (Btu/Wh):
-10	2,300	98.8	8.8	4.1
-5	2,620	100.1	10.1	4.4
0	2,970	101.5	11.5	4.7
5	3,360	103.0	13.0	5.1
10	3,790	104.7	14.7	5.4
15	4,260	106.5	16.5	5.8
20	4,760	108.4	18.4	6.2
25	5,290	110.4	20.4	6.5
30	5,860	112.6	22.6	6.9
35	6,440	114.8	24.8	7.2
40	7,060	117.1	27.1	7.6
45	7,690	119.5	29.5	7.9

Copyright © 2019 Emerson Climate Technologies, Inc. All rights reserved.